



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem



NOISE S.T.O.P. ACOUSTI-BOARD™

**Sound Deadening, Sound Absorbing,
Insulating, Low Cost**

- **Best Value!**
- **Fiberglass Free**
- **Easy to Install**

MATERIAL: Recycled Wood Fiber Residue.

PANEL SIZE: 2' x 4' or 4' x 8'

DENSITY: 15 to 20 lbs. Per Cubic Foot.

THICKNESS: 1/2 Inch.

WEIGHT: .65 lbs./sq. ft.

INSULATING VALUE: R=1.22 at 1/2" (ASTM C518)

NRC: .35 (ASTM C423)

STC: 26 (ASTM E-90)

APPLICATIONS: Acoustical-Board Can be Used as a Flooring Underlayment or as a Damping Layer Between Studs and Gypsum Board to Improve Sound Transmission Class (STC) of Gypsum Drywall Partitions. Schools, Apartments Buildings, Townhouses, Condominiums. Noise S.T.O.P. Acoustical-Board™ meets the Requirements of ASTM-C 208, the Specification for Cellulosic Fiber Insulating Board.

*Acousti-Board™
Meets the
Requirements of
ASTM-C 208, the
Specifications for
Cellulosic Fiber
Insulating Board.*

ACOUSTI-BOARD IS NOT FIRE RATED!

CAUTION: Noise S.T.O.P. Acousti-Board™ is Combustible and May Smolder if Ignited. Do Not Expose to Flame or Prolonged Excessive Heat Above 212° F without Sufficient Thermal Protection, or Use Between Layers of Noncombustible Material.

