

METALINE™ Acoustical Metal Ceiling Tiles









Sound Absorption / Noise Reduction

	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	STC
0.25 thick	0.37	0.59	0.30	0.50	0.75	1.09	0.55
0.50 thick	0.40	0.63	0.43	0.60	0.77	0.89	0.61

MATERIAL

Expanded perforated metal with melamine foam backing.

PATTERN

Standard, medium & ultra.

FEATURES

Expanded metal design.

SIZES

Nominal 24" x 24", 24" x 48".

THICKNESS

.25" or .50".

APPLICATIONS

Offices, conference rooms, board rooms, airports, lobbies, convention centers, retail stores, and more.

COLOR

White metal, chromed metal with colored backing inserts (light gray, charcoal gray and white).

INSTALLATION

Lay-in 15/16" T-bar grid system. Slight tegular edge.

FLAMMABITLY

Class 1 fire-rated for smoke density and flame spread.

Test Reports & Additional Information Can be Found at:

www.acousticalsurfaces.com/acoust_ceilings/square.htm

METALINE







METALINE Medium



METALINE Ultra

Metaline options continued on next page



METALINE™ Acoustical Metal Ceiling Tile

METALINE SMALL

OPTIONS

White or chrome metal with light-grey or charcoal insert.

PROFILE

Flat or beveled profile.

PANEL SIZES

24" x 24".

OPEN SURFACE

68.2%.



White Metal Light-Gray Insert



Chrome Metal Light-Grey Insert



White Metal Charcoal Insert



Chrome Metal Charcoal Insert

METALINE MEDIUM

OPTIONS

White or chrome metal with light-grey or charcoal insert.

PROFILE

Flat profile only.

PANEL SIZES

24" x 24" or 24" x 48".

OPEN SURFACE

62.5%.



Chrome Metal Light-Grey Insert



Chrome Metal Charcoal Insert

NOTE:

50 tile minimum order requires 12-14 week lead time.

METALINE LARGE

OPTIONS

White or Chrome Metal with Light-Grey or Charcoal Insert.

PROFILE

Flat profile only.

PANEL SIZES

24" x 24", 24" x 48" or 48" x 48".

OPEN SURFACE

71.4%.



Chrome Metal Light-Grey Insert



Chrome Metal Charcoal Insert

NOTE:

50 tile minimum order requires 12-14 week lead time.











ACOUSTICAL SURFACES, INC.

PAGE 3