Frost

Slate

Starlight

025

031

# **Tempest** 2120

# 

**Gold Rush** 

Sandstorm

Zebra 015



**Silk** 045



Ginger 042



Full Stream 012



**Tumbleweed** 030



**Dragonfly** 020



rempest 2120

# **Tempest** 2120

### **Specifications**

Content	100% pre-consumer recycled polyester
Weight	11.3 ± 1.0 oz./lin. yd.
Width	66" min. useable
Repeat	none


### Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

### **Acoustical Performance**

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

## Acoustical Performance for Panel Applications (ISO 10534-2)




NRC of anechoic termination	
NRC of fabric in front of anechoic termination	.95

### **Performance**

*	Colorfastness to Light (AATCC 16.3 Option 3)  Grade 4 min. at 40 hours
U	Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
×	Breaking Strength (ASTM D5034)  180 lbf min. warp and 160 lbf min. fill
*	Flammability (ASTM E84) Class I or A

### **Sustainability**



### **Miscellaneous**

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.

