



ACOUSTICAL
Sound Solutions for Over 35 Years

SURFACES INC.
Soundproofing | Acoustics | Noise & Vibration Control



Material Name: Fiber Glass Speciality Insulation

Material Safety Data
Sheet ID: 1001

Section 1 – Chemical Product and Company Identification

Product Name Fiber Glass Insulation
CAS# Not applicable
Generic Name Fiber Glass Wool Product
Formula Not available
Chemical Name: Mixture
Hazard Label FGW-01
Manufacturer Information
John Manville
Performance Materials Division
P.O. Box 5108
Denver, CO 80127 USA

Telephone: 303-978-2000 8:00AM-5PM M-F
Internet Address: <http://www.jm.com>
Emergency: 800-424-9300 (Chemtrec, In English)

Trade Names: Appliance Spin-Glas® (ASG); CM-24; CM-26; Spin-Glas® Board Equipment Insulation; Exact-O-Board®, Flex-Glas™ PC; Microlite® Microlite® AWP; Microlite® MW; Microlite® TC; Microlite® WH; Microlite® XP; Range Spin-Glas®; Spin-glas® All Types; Spin-Glas (SG) 22-32; Spin-Glas® Water Heater (SG-WH); Tuf-Skin®; Tuf-Skin II; Valulite™.

Section 2 – Composition / Information on Ingredients

| CAS# | Component | Percent |
|---------------|---|---------|
| 65997-17-3 | Fiber Glass Wool | 50-99 |
| 25104-55-6 | Urea extended phenol-formaldehyde resin (cured) | 1-20** |
| 25212-25-3 | Urea extended phenol-melamine formaldehyde binder (cured) | 1-20** |
| 1333-86-4 | Carbon black (encapsulated) | 0-20** |
| Not Available | Phenol-Formaldehyde binder (cured) | 1-6*** |

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Glass wool fiber.

Additional Component Information

*Carbon black is a component of some black products only and is encapsulated within binder or coatings. Note: Due to the product form, exposures to hazardous dusts or fumes are not expected to occur. Exposure limits are given for reference only.

**For trade names other than Range Spin-Glas®, binder may be any of these.

***Range Spin-Glas®

Some products have facings of kraft paper, vinyl, or other materials.

Section 3 – Hazards Identification

Emergency Overview

APPEARANCE AND ODOR: Fibrous glass blanket or board; white, gold-to yellow, orange, black or black with an amber or black core; with or without non-woven facings. No significant odor.

Inhalation of gases released during heat treatment or curing of this product may cause temporary upper respiratory irritation and/or congestion—remove affected individuals to fresh air.

Potential Health Effects

Summary

Breathing dust from this product may cause a scratchy throat, congestion, and slight coughing. Getting dust or fibers on the skin or in the eyes may cause itching, rash, or redness. Additional health and safety information is provided in Section 11 of this material safety data sheet.

Inhalation

Irritation of the upper respiratory tract (scratchy throat), coughing, and congestion may occur in extreme exposures.

Skin

Temporary irritation (itching) or redness may occur.



ACOUSTICAL

Sound Solutions for Over 35 Years

SURFACES INC.

Soundproofing | Acoustics | Noise & Vibration Control

Material Name: Fiber Glass Specialty Insulation

**Material Safety Data
Sheet ID: 1001**

Absorption

Not applicable.

Ingestion

This product is not intended to be ingested (eaten). if ingested, it may cause temporary irritation to the gastrointestinal (digestive) tract.

Eyes Temporary irritation (itching) or redness may occur.

Ears Temporary irritation (itching) or redness may occur.

Primary Routes of Entry (Exposure)

Inhalation (breathing dust), skin, and eye contact.

Target Organs

Nose (nasal passages), throat, lungs, skin, eyes.

Medical Conditions Aggravated by Exposure

Pre-existing chronic respiratory, skin, or eye diseases or conditions.

Section 4 – First Aid Measures

First Aid: Inhalation

Remove to fresh air. Drink water to clear throat, and blow nose to remove dust.

First Aid: Skin

Wash gently with soap and warm water to remove dust. Wash hands before eating or using the restroom.

First Aid: Ingestion

Product is not intended to be ingested or eaten. If this product is ingested, irritation of the gastrointestinal (GI) tract may occur, and should be treated symptomatically. Rinse mouth with water to remove fibers, and drink plenty of water to help reduce the irritation. No chronic effects are expected following ingestion.

First Aid: Eyes

Do not rub or scratch your eyes. Dust particles may cause the eye to be scratched. Flush eyes with large amounts of water for 5-15 minutes. if irritation persists, contact a medical professional.

First Aid: Ears

Do not rub or scratch the ear if itching occurs. Wash gently with soap and warm water to remove dust or fibers.

First Aid: Notes to Physician

This product is a mechanical irritant, and is not expected to produce any chronic health effects from acute exposures. Treatment should be directed toward removing the source of irritation with symptomatic treatment as necessary.

Section 5 – Fire Fighting Measures

Flash Point: Not applicable

Upper Flammable Limit (UFL): Not applicable

Auto Ignition: Not determined

Rate of Burning: Not determined

General Fire Hazards

There is no potential for fire or explosion.

Extinguishing Media

Carbon dioxide (CO₂), water, water fog, dry chemical.

Fire Fighting equipment/Instructions

No special procedures are expected to be necessary for this product. Normal fire fighting procedures should be followed to avoid inhalation of smoke and gases.

Method Used: Not applicable

Lower Flammable Limit (LFL): Not applicable

Flammability Classification: Not determined

Section 6 – Accidental Release Measures

General Fire Hazards

Pick up large pieces. Vacuum dusts. If sweeping is necessary, use a dust suppressant such as water. Do not dry sweep dust accumulation or use compressed air for clean-up. These procedures will help to minimize potential exposures.

Clean-Up Procedures

Avoid the generation of dusts during clean-up.



Material Name: Fiber Glass Specialty Insulation

Material Safety Data
Sheet ID: 1001

Section 7 - Handling and Storage

Handling Procedures

Use protective equipment as described in Section 8 of this material safety data sheet when handling uncontained material.

Storage Procedures

Warehouse storage should be in accordance with package directions, if any. Material should be kept dry, and protected from moisture.

Section 8 - Exposure Controls / Personal Protection

Exposure Guidelines

A: General Product Information

Glass wool fiber, OSHA voluntary Health and Safety Partnership Program (HSPP): 1f/cc TWA for fibers longer than 5 µm with a diameter less than 3µm.

B: Component Exposure Limits

Fiber Glass Wool (65997-17-3)

ACGIH: 1 f/cc TWA (respirable fibers: length > 5 µm aspect ratio equal to or greater than 3:1; (related to Glass wool fibers)

Carbon black (encapsulated) (1333-86-4)

ACGIH: 3.5 mg/m³ TWA
OSHA 3.5 mg/m³ TWA.

PERSONAL PROTECTION EQUIPMENT

Personal Protective Equipment: Eyes/Face

Safety glasses with sideshields are recommended to keep dust out the eyes.

Personal Protective Equipment: Ears

Use ear protection (earplugs, hood, or earmuffs) to prevent airborne dust or fibers from entering the ear.

Personal Protective Equipment: Skin

Leather or cotton gloves should be worn to prevent skin contact and irritation. Barrier creams may also be used to reduce skin contact and irritation caused by fiber glass.

Personal Protective Equipment: Respiratory

A respirator should be used if ventilation is unavailable, or is inadequate for keeping dust and fiber levels below the applicable exposure limits. In those cases, use a NIOSH-certified disposable or reusable particulate respirator with an efficiency rating of N95 or higher (under 42 CFR 84) when working with this product. For exposures up to five times the established exposure limits use a quarter-mask respirator (e.g., MSA's DM-11, Racal's Delta N95 or higher. Operations such as sawing, blowing, tear out, and spaying may generate airborne fiber concentrations requiring a higher level of respiratory protection. For exposures up to 50 times the established exposure limits use a full-face respirator, rated N99 or higher.

Ventilation

In fixed manufacturing settings, local exhaust ventilation should be provided at areas of cutting to remove airborne dust and fibers. General dilution ventilation should be provided as necessary to keep airborne dust and fibers below the applicable exposure limits and guidelines. The need for ventilation systems should be evaluated by a professional industrial hygienist, while the design of specific ventilation systems should be conducted by a professional engineer.

Personal Protection Equipment: General

Wear a cap, a loose-fitting, long-sleeved shirt and long pants to protect skin from irritation. Exposed skin areas should be washed with soap and warm water after handling or working with fiber glass. Clothing should be washed separately from other clothes, and the washer should be rinsed thoroughly (run empty for a complete wash cycle). This will reduce the chances of fiber glass being transferred to other clothing.



Material Name: Fiber Glass Specialty Insulation

Material Safety Data
Sheet ID: 1001**Section 9 – Physical & Chemical Properties**

| | | | |
|-------------------------------------|--|--------------------------|---------------------|
| Appearance: | White, gold to yellow, orange, black or black with an amber core; fibrous glass blanket or board | Odor: | No significant odor |
| Physical State: | Solid | pH: | Not applicable |
| Vapor Pressure: | Not applicable | Vapor Density: | Not applicable |
| Boiling Point: | Not applicable | Melting Point: | >704°C/1300°F |
| Solubility (H₂O): | Nil | Specific Gravity: | Variable |
| Freezing Point: | Not applicable | Evaporation Rate: | Not applicable |
| Percent Volatile: | 0 | VOC: | Not applicable |

Section 10 – Chemical Stability & Reactivity Information**Chemical Stability**

This is a stable material. This product is not reactive.

Hazardous Decomposition

The decomposition products from this material are those that would be expected from any organic (carbon-containing) material, and are mainly derived from pyrolysis, or burning, of the resin. These decomposition products may include carbon monoxide, carbon dioxide, carbon particles, and traces of hydrogen cyanide.

Hazardous Polymerization

Will not occur.

Section 11 – Toxicological Information**Acute Toxicity****A: General Product Information**

Dust from this product is a mechanical irritant, which means that it may cause temporary irritation or scratchiness of the throat, and/or itching or the eyes and skin.

B: Component Analysis - LD50/LC50

Urea extended phenol-formaldehyde resin (cured) (25104-55-6)

Oral LD50 Rat: 7 g/kg; Oral LD50 Mouse: 7 g/kg

Carbon black (encapsulated) (1333-86-4)

Oral LD50 Rat: >15400 mg/kg; Dermal LD50 Rabbit: >3 g/kg

Carcinogenicity**Component Carcinogenicity****Fiber Glass Wool (65997-17-3)**

ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans (related to Glass wool fibers)

NTP: Reasonably anticipated to be a Carcinogen (respirable size) (related to Glasswool) (Possible select Carcinogen)

IARC: Group 3 - Not Classifiable (IARC Monograph 43, 1988; Monograph 81, 2002, related to insulation glass wool)

Carbon black (encapsulated) (1333-86-4)

ACGIH: A4 - Not classifiable as a Human Carcinogen

IARC: Group 2B - Possibly Carcinogenic to Humans (IARC Monograph 65, 1996)

Chronic Toxicity

Fiber Glass Wool: In October 2001, IARC classified fiber glass wool as Group 3, "not classifiable as to its carcinogenicity to humans." The 2001 decision was based on current human and animal research that shows no association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease. This is a reversal of the IARC finding in 1987 of a Group 2B designation (possibly carcinogenic to humans) based on earlier studies in which animals were injected with large quantities of fiber glass. NTP and ACGIH have not yet reviewed the IARC reclassification or the most current fiber glass health research; at this time, both agencies continue to classify glass wool based on the earlier animal injection studies.

A detailed listing of references on fiber glass health effects can be found in the publication HSE-64C, "Health and Safety Aspects of Fiber Glass", which can be downloaded from Johns Manville's internet homepage, www.jm.com (select "Health Safety and Environment").



Material Name: Fiber Glass Specialty Insulation

Material Safety Data
Sheet ID: 1001

Section 12 – Ecological Information

Ecotoxicity

A: General Product Information

No data available for this product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

No ecotoxicity data are available for this product's components.

Section 13 – Disposal Considerations

US EPA Waste Number & Descriptions

A: General Product Information

This product, as supplied, is not regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Comply with state and local regulations for disposal. If you are unsure of the regulations, contact our local Public Health Department, or the local office of the EPA.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 – Transportation Information

Shipping Name: This product is not classified as a hazardous material for transport.

Section 15 – Regulatory Information

US Federal Regulations

A: General Product Information

SARA 311 Status. The following SARA 311 designations apply to this product: Delayed (chronic) health hazard.

B: Component Analysis

None of this product's components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 DFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

No information available for this product.

B: Component Analysis – State

The following components appear on one or more of the following state hazardous substance lists:

| Component | CAS # | CA | FL | MA | MN | NJ | PA |
|--|------------|------------------|----|------------------|-----|-----|------------------|
| Fiberglass Wool (*related to Mineral wool fiber) (*related to Glass wool fiber) | 65997-17-3 | Yes ¹ | No | Yes ¹ | Yes | No | Yes ² |
| Carbon black (encapsulated) | 1333-86-4 | Yes | No | Yes | Yes | Yes | Yes |

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):
WARNING! this product contains a chemical know to the State of California to cause cancer.

Other Regulatory Information

A: General Product Information

B: TSCA Status

This product and its components are listed on the TSCA 89(b) inventory.

None of the components listed in this product are listed on the TSCA Export Notification 12(b) list.

C: Component Analysis – Inventory

| Component | CAS# | TSCA | DSL | EINECS |
|---|------------|------|-----|--------|
| Fiber Glass Wool | 65997-17-3 | Yes | Yes | Yes |
| Urea extended phenol-melamine formaldehyde binder (cured) | 25212-25-6 | Yes | No | No |
| Urea extended phenol-formaldehyde binder (cured) | 25104-55-6 | Yes | Yes | No |
| Carbon black (encapsulated) | 1333-86-4 | Yes | Yes | Yes |



Material Name: Fiber Glass Specialty Insulation

Material Safety Data
Sheet ID: 1001

International Regulations

A: General Product Information
Not information available.

B: Component Analysis - WHMIS IDL

| Component | CAS# | Minimum Concentration |
|-----------------------------|-----------|---|
| Carbon black (encapsulated) | 1333-86-4 | 1% (English Item 309, French Item 1271) |

Section 16 - Other Information

Other Information

Prepared for
John Manville
Performance Materials
P.O. Box 5108
Denver, CO USA 80217-5108

Prepared by:
Johns Manville Technical Center
P.O. Box 625005
Littleton, CO USA 80162-5005

The information herein is presented in good faith and believed to be accurate as the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This is the end of MSDS # 1001