



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problems

Spec Data Sheet

MLVB1-Re SERIES FLEXIBLE NOISE BARRIERS

MLVB1-Re Noise Barrier

MLVB1-Re is a flexible **reinforced** loaded vinyl noise barrier featuring an internal reinforcement to offer maximum tear strength and durability. MLVB1-Re Panels can be used where a noise barrier wall is required. It is also commonly used in conjunction with Quilted Fiberglass Absorbers to form BBC style acoustical curtain composites.

MLVB1-Re is also available in a USDA approved grade.

- Rolls are available 54" wide up to 60' long
- Curtain Panels available with grommets and Velcro
- Limp, flexible, formable, versatile
- High tear and tensile strength, Extremely durable



Applications:

Typically used where a rugged, tear resistant noise barrier is required. Also used as a barrier back material in BBC style Acoustical Curtain Panels in an Acoustical Curtain Enclosure, acoustical jacket or wrap, and to serve as an accordion fold acoustical door. Suitable for outdoor use. Available in gray, tan, blue or olive.

Product Data:

Description	one pound per square foot reinforced loaded vinyl barrier
Nominal thickness	0.107 inches
Standard width	54" wide
Roll length	60' long
Weight	1.0 lb psf
Tensile (PSI)	900 lb/ in ²
Tear (pound force)	70 lb/ in.
Service Temperature	-20° F to +180°

Acoustical Performance:

Sound Transmission Loss

Product	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
MLVB1-Re	13	17	22	26	32	37	26

Per ASTM E-90 & E 413