



# Acoustical Surfaces, Inc.

**SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

**We Identify and S.T.O.P. Your Noise Problems**

## **BLACK FACING** **For Quiet Liner™**

### **Dry Laid Web, Chemically Bonded with Acrylic Latex**

**PRODUCT**

**DESCRIPTION:** Dry laid web, chemically bonded with acrylic latex. Web is comprised of polyester and rayon fibers treated with flame retardant, water repellent, and antimicrobial agents. Finished fabric is scatter coated with polyethylene adhesive.

**WIDTH**

**TOLERANCE:** 49.0 +/- 0.5 inches.

**YARDS/ROLL:** 1000.

	<b>PHYSICALS</b>	<b>Min.</b>	<b>Max.</b>
BASE PRODUCT WGT: (GRAMS SQ/YD)	54.0	48.6	59.4
THICKNESS, MILS:	8.0	7.0	9.0
TENSILES: GRAB (ASTM D1117-77)			
MD:	21.0	16.0	NA
XD	7.5	4.5	NA
ADHESIVE WGT (GRAMS SQ/YD)	8.0	7.0	9.0