



# Acoustical Surfaces, Inc.

**SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

---

---

**We Identify and S.T.O.P. Your Noise Problems**

## MATERIAL SAFETY DATA SHEET

MSDS Name: Green Series(tm) Construction Adhesive

MSDS Number: 1020004

Version Number 2

Revision Date: APR-16-2009

Page Number: 1

-----

### SECTION I - PRODUCT AND COMPANY INFORMATION

**Product Name:** Green Series(tm)  
Construction Adhesive

**HMIS Hazard Rating:** Health: 1 Fire: 0 Reactivity: 0 PPE: B

**Company Identification:** Rendered by Manufacturer and Released to:  
Acoustical Surfaces, Inc.  
123 Columbia Court North  
Chaska, MN 55318

**Contact:** Consumer Help (800) 448-0121  
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)  
(800) 424-9300  
in Canada CANUTEC 613-996-6666

**Product Class** ADHESIVE  
**Trade Name** GREEN SERIES  
**Product Code** see above

### SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
ETHYLENE GLYCOL	107-21-1	< 2.0	Y

**Ingredient Notes:**  
Remaining ingredients are not considered OSHA hazardous.

-----

### SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

**Form:** Off-white Mastic

**Solubility (in water):** YES

**pH Value, +/- .3:** 7.5

**Boiling Range:** 212.°F (100.°C)

**Vapor Pressure (mmHg):** 15.@ 68.°F (20.°C)

**Evaporation Rate:** 0.6 times Slower than n-Butyl Acetate

**Vapor Density:** Heavier than air

**% Volatile, Weight** 30.%  
**% Volatile, Volume** Approx 45.%  
**Specific Gravity:** 1.121  
**VOC (less H2O or exempt)** under 0.1%wt

**NOTE:**

-----



# Acoustical Surfaces, Inc.

**SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318  
(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121  
Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)  
Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

**We Identify and S.T.O.P. Your Noise Problem**

## MATERIAL SAFETY DATA SHEET

MSDS Name: Green Series(tm) Construction Adhesive  
MSDS Number: 1020004  
Version Number: 2  
Revision Date: APR-16-2009  
Page Number: 2

Odor : Mild acrylic odor. Freeze Point : 32 Deg F

### SECTION IV - FIRE FIGHTING MEASURES

Flammability Class: N/A  
Flash Point: none  
Explosive Range (LEL/UEL): Not Applicable

### EXTINGUISHING MEDIA:

Dry chemical -- Carbon Dioxide -- Foam -- Water Fog  
Will not burn in wet state.

### SPECIAL FIRE-FIGHTING PROCEDURES:

Water may be used to cool and protect exposed containers.  
Caution should be taken because uncured material is water soluble.

### UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may burst when exposed to extreme heat or fire.

### SECTION V - HEALTH HAZARD DATA

Route	Species	Exposure and Dose
		LD50 7000. PPM

### ROUTES OF ENTRY:

ENTRY THROUGH...Inhalation and skin most likely

### CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OSHA? NO

### EFFECTS OF OVEREXPOSURE

Inhalation: May cause nose or throat irritation.  
Skin/Eye Contact: May cause irritation.  
Ingestion: Swallowing large amounts may cause nausea, vomiting. ( an unlikely route of entry )

### FIRST AID MEASURES

Inhalation: If affected by inhalation, remove to fresh air.  
Eye Contact: Flush with water for at least 15 minutes, and get prompt medical attention.  
Skin Contact: Wash skin thoroughly with soap and water.  
Ingestion: Drink water, and get medical attention.

N/A= Not applicable N/AV=Not available N/E, N/est=Not established

### CHRONIC HAZARDS

Swallowing ETHYLENE GLYCOL may cause gastrointestinal irritation.



# Acoustical Surfaces, Inc.

**SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

## We Identify and **S.T.O.P.** Your Noise Problem

### MATERIAL SAFETY DATA SHEET

MSDS Name: Green Series(tm) Construction Adhesive

MSDS Number: 1020004

Version Number 2

Revision Date: APR-16-2009

Page Number: 3

#### SECTION VI - STABILITY AND REACTIVITY

Stability: Product is stable under normal storage conditions

Hazardous Polymerization: Will not occur under normal conditions

#### INCOMPATIBILITY:

None

#### CONDITIONS TO AVOID:

None

#### HAZARDOUS DECOMPOSITION PRODUCTS:

May produce oxides of carbon and oxides of nitrogen when burned.

#### SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

##### STEPS TO BE TAKEN IN CASE OF SPILL:

Wear appropriate protective clothing. Add dry absorbent and shovel or sweep up. Place in an appropriate container and seal.

##### WASTE DISPOSAL METHOD:

Dispose of in accordance with Federal, State, and Local regulations.

#### SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
ETHYLENE GLYCOL	N/est	100.00 mg/M3	N/est	N/est	50.00 PPM

##### RESPIRATORY PROTECTION:

NIOSH respirators recommended if vapors and mists are generated.

##### VENTILATION:

Local exhaust is recommended for safe practice.

##### PROTECTIVE CLOTHING:

Gloves and clothing should be worn to prevent repeated skin contact.

##### EYE PROTECTION:

Eye protection should be worn.

##### HANDLING AND STORAGE PRECAUTIONS:

Keep from freezing. Keep away from heat.

Keep containers closed when not in use.

Avoid prolonged or repeated contact with skin.

Keep out of the reach of children.

#### SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

##### GROUND TRANSPORT (DOT) - DOMESTIC



# Acoustical Surfaces, Inc.

**SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

**We Identify and S.T.O.P. Your Noise Problem**

## MATERIAL SAFETY DATA SHEET

MSDS Name: Green Series(tm) Construction Adhesive

MSDS Number: 1020004

Version Number 2

Revision Date: APR-16-2009

Page Number: 4

-----  
Latex Adhesive, Not Regulated

**AIR TRANSPORT (DOT) - DOMESTIC**

Latex Adhesive, Not Regulated

**AIR TRANSPORT ( IATA ) - INTERNATIONAL**

Latex Adhesive, Not Regulated

**MARINE - OCEAN TRANSPORT ( IMDG )**

Latex Adhesive, Not Regulated

-----  
**SECTION X - REGULATORY INFORMATION:**

**SARA TITLE III SECTION 313:**

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
ETHYLENE GLYCOL	107-21-1	< 2.0

Ethylene Glycol fits the EPA Hazard Category definition of Immediate (Acute) and Delayed (Chronic) Health Hazards under SARA Sect.311,312. All chemical substances are TSCA listed.

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**DISCLAIMER:**

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.

-----  
Last Page