



**MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: **DA5 Max Performance MP Carpet & Sheet Vinyl Adhesive**

W.H.M.I.S. CLASSIFICATION: NON-CONTROLLED

PRODUCT USES: For installing a wide variety of floor covering materials

V.O.C. CONTENT: 0 Calculated

**SECTION I-MANUFACTURER IDENTIFICATION**

Rendered by Manufacturer and released to: Acoustical Surfaces Inc.  
 Address: 123 Columbia Court North, Suite 201, Chaska, MN 55318  
 24 HOUR (CANUTEC) Phone: (613) 996-6666  
 DATE REVISED: 03/01/04

NAME OF PREPARER:  
 INFORMATION PHONE:  
 SOURCES USED: Raw material supplier  
 M.S.D.S., US M.S.D.S.

**SECTION II-HAZARDOUS INGREDIENTS INFORMATION**

COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50
NO REPORTABLE INGREDIENTS					

**SECTION III-PHYSICAL DATA**

BOILING POINT: 100°C  
 VAPOR DENSITY (AIR=1):  
 VAPOR PRESSURE (MM OF MERCURY):  
 SOLUBILITY IN WATER  
 APPEARANCE AND ODOR:

FREEZING POINT: N/A  
 Heavier than air  
 As for water.  
 Miscible  
 Beige, soft buttery paste,  
 very mild resinous odor.

SPECIFIC GRAVITY (H2O=1): 1.2 pH: 9-10  
 EVAPORATION RATE (BUTYL ACETATE=1): Slower  
 EVAPORATION RATE (ETHYL ACETATE=1): Slower  
 PERCENT VOLATILE: 42

ODOR THRESHOLD (PPM): Not available

**SECTION IV-FIRE AND EXPLOSION DATA**

FLASHPOINT (specify method): None  
 FLAMMABLE LIMITS (% BY VOLUME):  
 FIRE EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical  
 SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product.  
 UNUSUAL FIRE AND EXPLOSION HAZARDS: None

METHOD USED:  
 LOWER: N/A UPPER N/A  
 AUTO IGNITION TEMP: N/A

IMPACT SENSITIVITY: Insensitive  
 SENSITIVITY TO STATIC DISCHARGE: Insensitive  
 TDG FLAMMABILITY CLASSIFICATION: Not regulated

**SECTION V-REACTIVITY DATA**

STABILITY: Staple  
 INCOMPATIBILITY (Materials to avoid): Strong oxidizers and caustics  
 HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2 and Hydrocarbons upon combustion  
 HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Excessive Heat

CONDITIONS TO AVOID: None

**SECTION VI-TOXICOLOGICAL PROPERTIES**

**ENTRY ROUTE TABLE**

SKIN CONTACT	SKIN ABSORPTION	EYE CONTACT	INHALATION ACUTE	INHALATION CHRONIC	INGESTION
--------------	-----------------	-------------	------------------	--------------------	-----------

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Product may irritate eyes and skin. Ingestion: Causes vomiting, diarrhea, depressed respiration.  
 EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Skin chapping.

LD50 (SPECIFY SPECIES & ROUTE): Not Available	LD50 (SPECIFY SPECIES): Not Available	EXPOSURE LIMIT: Not Available	IRRITANCY: None
SENSITIZING CAPACITY: None	CARCINOGENICITY: None	REPRODUCTIVITY EFFECTS: None	SYNERGISTIC MATERIALS: None Known

**SECTION VII-PREVENTIVE MEASURES**

RESPIRATORY PROTECTION (SPECIFY TYPE): None  
 VENTILATION: None should be required.  
 PROTECTIVE GLOVES: None EYE PROTECTION: Goggles  
 OTHER PROTECTIVE EQUIPMENT: None required.  
 SPILL PROCEDURES: Mechanically collect. Wash area with water. Prevent from entering sewers or waterways. Spilled material may cause slippery conditions. Promptly report significant spills with appropriate authorities. Consult local regulations.  
 WASTE DISPOSAL METHOD: Destroy by incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.  
 STORAGE & HANDLING PRECAUTIONS: Keep containers from excessive heat and freezing. Keep out of reach of children.  
 OTHER PRECAUTIONS: None.

**SECTION VIII-FIRST AID MEASURES**

EYES: Flush with water for 20 minutes, holding eyelids open. Seek medical attention.  
 SKIN: Wash with soap and water. Seek medical attention if irritation develops.  
 INGESTION: Do not induce vomiting. If victim is conscious give milk or water. Contact physician immediately.