# **Felt**

# 9900



Pear

3210

Aegean

**Azalea** 3049

3051





Maize 3204



Saffron 3367



Cherry



White\*



**Aluminum** 3055



Sky 3052



Liberty 3053



lvory 3206



Dune 3062



Pebble 3056



Deep Sea 3054





Latte 3063



Mink 3066



**Ebony** 3059

# **Felt** 9900

## **Specifications**

80% polyester 20% post-consumer recycled polyester
10.2 ± 1.0 oz./lin. yd.
64" min. useable
none


# **Cleaning Code**

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

### **Acoustical Performance**

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

#### **Acoustical Performance for Panel Applications** (ISO 10534-2)



NRC of anechoic termination 1.00 NRC of fabric in front of anechoic termination 0.99

### **Performance**

Colorfastness to Light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours Colorfastness to Crocking (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet



Breaking Strength (ASTM D5034)

130 lbf min. warp and 95 lbf min. fill



Flammability (ASTM E84) ASTM E84 Class I or A

#### Miscellaneous

Proudly made in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a non-directional fabric.

\* Light fabric are subject to transparency issues depending on lighting intensity and internal structure. Application testing of this product is recommended.

This product is a **Feltväri**™ non-woven.

Visit guilfordofmaine.com for samples.



program. Additional testing of this U.L. recognized component fabric is not required on approved panels from participating manufacturers.

USA & INTERNATIONAL

800 544 0200 PHONE