Framework 2762

Sandy Pebble

Eucalyptus

Elephant

2554





Chamois 2552



Beige 2687



Cappuccino 2832



Capri

2831

2689



Gray Blue 2553

Stone

2688



Blue Smooth 2519



Espresso

Framework 2762

Specifications

| Content | 100% polyester |
|---------|------------------------|
| Weight | 9.5 ± 0.5 oz./lin. yd. |
| Width | 66" min. useable |
| Repeat | none |
| | |


Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Acoustical Performance

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

Acoustical Performance for Panel Applications (ISO 10534-2)



| NRC of anechoic termination | |
|--|-----|
| NRC of fabric in front of anechoic termination | .90 |

Performance

| * | Colorfastness to Light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours |
|---|--|
| U | Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet |
| × | Breaking Strength (ASTM D5034) 150 lbf min. warp and 125 lbf min. fill |
| * | Flammability (ASTM E84) Class I or A |

Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.

