




**ACOUSTICAL SURFACES INC.**  
*Sound Solutions for Over 40 Years* | Soundproofing | Acoustics | Noise & Vibration Control



96D Allen Blvd.,  
 Farmingdale, NY 11735  
 TEL: (631) 293-8944  
 FAX: (631) 293-8956  
 Page 1

|  |   |  |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
|--|---|--|-----|-----------------|-------------------------|--------------------|-----------------|--------------|--------------|--|--------------------|-----------------|--------------|--------|-------------|---------------|---------|-------------|----------------|----------|-------------|
| Received: 05/23/2001   | Completed: 06/14/2001   | Letter: O                                  | rb  | P.O.: 508-00150 | Test Report: 2-34994-0- |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
| Client's Identification  | Style: 2721 Streetwise. Fiber Content: 100% Polyester. Width: 66. Finish: 02 (water)  |  |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
| Tested For:  | Rendered by Manufacturer and Released to:<br>Acoustical Surfaces, Inc.<br>123 Columbia Court North, Suite 201<br>Chaska, MN 55318 | Key Test: ASTM E 84                        | 715 |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
|  |   | Tel: 1-800-527-6253<br>Fax: 1-952-448-2613 |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
|  |   | CODE: 7506506005501-4                      |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
| <p>TEST PERFORMED: ASTM E 84 – Standard Test Method for Surface Burning Characteristics of Building Materials. *</p> <p>APPROXIMATE THICKNESS OF SPECIMEN (as measured by Govmark): 0.028"</p> <p>PRODUCT CATEGORY: <input type="checkbox"/> Textile Product: <input type="checkbox"/> Non Textile Product</p> <p>* Note: Textile wallcoverings classified by this procedure are limited to use in sprinklered areas in certain public occupancies. If textile wallcoverings are used in non-sprinklered areas, a room/corner fire test is mandated.</p> <p>SPECIMEN CONDITIONING: The item tested was placed in a conditioned atmosphere of 73.4°F ± 5°F, and 50% ± 5% RH until equilibrium was reached.</p> <p>SPECIMEN MOUNTING:</p> <p><input type="checkbox"/> Adhered: The test specimen was bonded to three 1/4" GRC (Glass Reinforced Concrete) boards (a cement asbestos substitute) to form a test specimen the face of which was 20" x 24'.</p> <p><input checked="" type="checkbox"/> Unadhered: The 20" x 24' specimen was not adhered to any substrate. Instead, it was laid over a 2" hexagonal wire mesh screen and 1/4" rods.</p> <p>RESULTS:</p> <table border="0"> <tr> <td>Flame Spread Index</td> <td>Smoke Developed</td> </tr> <tr> <td>-----10-----</td> <td>-----95-----</td> </tr> </table> <p>CODE CLASSIFICATION SYSTEM:</p> <table border="0"> <tr> <td></td> <td>Flame Spread Index</td> <td>Smoke Developed</td> </tr> <tr> <td>Class I or A</td> <td>0 - 25</td> <td>450 or Less</td> </tr> <tr> <td>Class II or B</td> <td>26 - 75</td> <td>450 or Less</td> </tr> <tr> <td>Class III or C</td> <td>76 - 200</td> <td>450 or Less</td> </tr> </table> <p>CONCLUSION: Based on the above Results and Code Classification System the item tested is assigned a:</p> <p><input checked="" type="checkbox"/> Class I or A rating: <input type="checkbox"/> Class II or B rating: <input type="checkbox"/> Class III or C rating.</p> <p>REMARKS: None.</p> <p>DATA SUMMARY:</p> <p>Title to Ignition: 0.08 minutes<br/>     Maximum Flame Spread "Distance": 2.28 feet<br/>     Maximum Flame Spread "Time": 0.50 minutes</p> <p>CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by ASTM E 84.</p> <p></p> <p>_____<br/>     AUTHORIZED SIGNATURE<br/>     THE GOVMARK ORGANIZATION, INC.<br/>     CT jd</p> |   |  |     |                 |                         | Flame Spread Index | Smoke Developed | -----10----- | -----95----- |  | Flame Spread Index | Smoke Developed | Class I or A | 0 - 25 | 450 or Less | Class II or B | 26 - 75 | 450 or Less | Class III or C | 76 - 200 | 450 or Less |
| Flame Spread Index   | Smoke Developed   |  |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
| -----10-----   | -----95-----  |  |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
|  | Flame Spread Index  | Smoke Developed                            |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
| Class I or A   | 0 - 25  | 450 or Less                                |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
| Class II or B  | 26 - 75   | 450 or Less                                |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |
| Class III or C   | 76 - 200  | 450 or Less                                |     |                 |                         |                    |                 |              |              |  |                    |                 |              |        |             |               |         |             |                |          |             |